

[ 1 ] **EU-TYPE EXAMINATION CERTIFICATE**

[ 2 ] Equipment or protective system intended for use in potentially explosive atmospheres – Directive 2014/34/EU

[ 3 ] EU-type examination certificate Number: **CETS 23 ATEX 038 X** Issue:0

[ 4 ] Product: **Explosion-proof control, monitoring and signalling units**

Series: **CSA..., CSAX..., CSAP... .**

[ 5 ] Manufacturer: **Selection of Safety FZ-LLC**

[ 6 ] Address: **B12-232, Academic Zone01-Business Center 5, RAKEZ Business Zone-FZ, RAK, United Arab Emirates**

[ 7 ] This product any of acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

[ 8 ] The Certification body SIA «CE-Test», notified body number 2861 in accordance with Article 17 of the Directive 2014/34/EU of European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres, given in Annex II to the Directive.

The examination and test results are recorded in confidential Evaluation report number 038/2023 from 14.04.2023.

[ 9 ] Compliance with Essential Health and Safety Requirements has been assured by compliance with: EN IEC 60079-0:2018, EN 60079-1:2014, EN IEC 60079-7:2015/A1:2018, EN 60079-11:2012, EN 60079-31:2014

[ 10 ] If the sign «X» is placed after the certificate number, it indicates that the product is subject to Specified Conditions of Safe Use specified in the schedule to this certificate

[ 11 ] This EU-Type Examination Certificate relates only to the design and construction of the specified product in accordance to the Directive 2014/34/EU. Further requirements of the directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.

[ 12 ] The marking of the equipment or protective system shall include the following:



Ex marking	Series
Ⓜ II 2 G Ex db eb IIC T6, T5 or T4 Gb or Ⓜ II 2 G Ex db eb ib IIC T6, T5 or T4 Gb or Ⓜ II 2 D Ex tb IIIC T80°C, T95°C or T130°C Db	for CSA
Ⓜ IM 2 Ex db eb IMb or Ⓜ IM 2 Ex db eb ib IMb or Ⓜ II 2 G Ex db eb IIC T6, T5 or T4 Gb or Ⓜ II 2 G Ex db eb ib IIC T6, T5 or T4 Gb or Ⓜ II 2 D Ex tb IIIC T80°C, T95°C or T130°C Db	for CSAX
Ⓜ IM 2 Ex db eb IMb or Ⓜ IM 2 Ex db eb ib IMb or Ⓜ II 2 G Ex db eb IIC T6 or T5 Gb or Ⓜ II 2 G Ex db eb ib IIC T6 or T5 Gb Ⓜ II 2 D Ex tb IIIC T80°C or T95°C Db	for CSAP

Date of Certificate: 17.04.2023

Responsible person: Ing. Pavlo Khorunzhyy  
 Head of certification body





[ 13 ] SCHEDULE

[ 14 ] EU-TYPE EXAMINATION CERTIFICATE: **CETS 23 ATEX 038 X** Issue: 0

[ 15 ] Description of Product

CSA..., CSAX..., CSAP units are a shell consisting of a cover and a body, controls are located on the cover. Shell material: aluminum alloy, AISI 321, 316 stainless steel or polyamide. Entry into the enclosure is carried out through certified cable glands. Explosion-proof control elements, terminals and other explosion-proof devices that have valid certificates of conformity according to 2014/34 ATEX Directive are installed in control stations made with “explosion protection type “e””.

Table 1 - Technical characteristics of CSA..., CSAX..., CSAP series units.

Name of indicator, unit of measurement	Value
Switched current AC/DC, A	800
Switched voltage AC/DC, V	1000
Ambient temperature range, °C	for T6 - from -60 °C to + 80°C for T5 - from - 60°C to + 95°C for T4 - from - 60°C to + 130°C
The degree of protection of the shell in accordance with IEC 60529:2013	IP66

Table 2 - Body material CSA..., CSAX..., CSAP series boxes.

Series boxes	Group of application	Material
Series CSA	For group II and III	Aluminum alloy
Series CSAX	For group I, II and III	Stainless steel.
Series CSAP	For group I, II and III	Polyamide

For a more detailed description of the design, please refer to the relevant instruction manual.

[ 16 ] Test Report

The examination and test results are recorded in confidential Evaluation Report number 038/2023 from 14.04.2023

[ 17 ] Specific conditions of use

- electrical connectors (terminals), etc. must be installed in accordance with the manufacturer's instructions;
- when installing explosion-proof devices in explosive dusty environments, it is necessary to carry out cleaning to prevent the accumulation of excess dust, more than 5 mm on the surface of the housing;
- installation, connection and laying of cables is carried out with the power supply disconnected;

Certificate without signature are void. This certificate may only be reproduced in its entirety and without any change, schedule included.



- installation and operation of heating cables should be carried out by persons who know the rules for the operation of electrical installations in explosive areas, who have read the operation manual;
- the equipment must be used with certified cable glands, adapters, plugs, drainage devices and terminal blocks providing the required type and level of explosion protection.

[ 18 ] Essential health and safety requirements

The Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9.

Additional information: None.

[ 19 ] Drawings and Documents

The documents are listed in the Evaluation report number 038/2023 from 14.04.2023

Title Technical Documents	Decimal number	Date
CSA, CSAX, CSAP Operation Manual	640000255000.1	2023
Drawing of series CSA	640000252000	-
Drawing of series CSAX	346400560000	-
Drawing of series CSAP	346400580000	-
Method for calculating the maximum number of terminals	346400334901.1	2023